

Model	HDI-600S	HDI-600S+	HDI-600H
Max. size	660 × 560 mm		
Min. size	100 × 160 mm		
Plate loading	Manual mounting, auto loading		
Resolutions	4800/5080 dpi	4800/5080/9600 dpi	
※ S series speed	1.1~2.5 m ² /H (4500~2000Mj/cm ²) 4800/5080dpi	1.0~1.5 m ² /H (4500~2000Mj/cm ²) 9600dpi (S+)	
※ H series speed	2.0~4.5 m ² /H (4500~2000Mj/cm ²) 4800/5080dpi	2.0~2.4 m ² /H (4500~2000Mj/cm ²) 9600dpi	
Laser wavelength	830 nm		
Plate type	digital photopolymer plates, ablative films and polyester-base letterpress plates.		
MAX.plate thickness	≤3.94mm		
MIN.plate thickness	≥0.14mm		
Net weight	900 Kg		
Power supply	Single phase AC 220V ±5% 50/60Hz		
Rated Power	Approx.5.5KW(including vacuum pump & dedusting pump)		
Dimension	1375×1250×1115 mm (W×L×H)		
Environment	18-25°C; RH: 40%-60%		



Model	HDI-900S	HDI-900S+	HDI-900H
Max. size	920 × 730 mm		
Min. size	100 × 160 mm		
Plate loading	Manual mounting, auto loading		
Resolutions	4800/5080 dpi	4800/5080/9600 dpi	
※ S series speed	1.1~2.5 m ² /H (4500~2000Mj/cm ²)	4800/5080dpi	1.0~1.7 m ² /H (4500~2000Mj/cm ²) 9600dpi (S+)
※ H series speed	2.2~4.8 m ² /H (4500~2000Mj/cm ²)	4800/5080dpi	1.7~2.5 m ² /H (4500~2000Mj/cm ²) 9600dpi
Laser wavelength	830 nm		
Plate type	digital photopolymer plates, ablative films and polyester-base letterpress plates.		
MAX.plate thickness	≤3.94mm		
MIN.plate thickness	≥0.14mm		
Net weight	1300 Kg		
Power supply	Single phase AC 220V±5% 50/60Hz		
Rated Power	Approx.5.7KW(including vacuum pump & dedusting pump)		
Dimension	1650×1205×1077 mm (W×L×H)		
Environment	18~25°C; RH: 40%~60%		



Model	HDI-1600S	HDI-1600S+	HDI-1600H
Max. size	1524 × 1200 mm		
Min. size	200 × 200 mm		
Plate loading	Manual mounting, auto loading		
Resolutions	4800/5080 dpi	4800/5080/9600 dpi	
※ S series speed	1.0-2.4 m ² /H (4500-2000Mj/cm ²)	4800/5080dpi	1.0-1.6 m ² /H (4500-2000Mj/cm ²) 9600dpi (S+)
※ H series speed	2.0-4.6 m ² /H (4500-2000Mj/cm ²)	4800/5080dpi	1.6-2.4 m ² /H (4500-2000Mj/cm ²) 9600dpi
Laser wavelength	830 nm		
Plate type	digital photopolymer plates, ablative films and polyester-base letterpress plates, Metal matrix flexo plate		
MAX.plate thickness	≤3.94mm		
MIN.plate thickness	≥0.14mm		
Net weight	1500 Kg		
Power supply	3-phase AC 380V±5% 50/60Hz		
Rated Power	Approx.7KW(including vacuum pump & dedusting pump)		
Dimension	2170×1250×1077 mm (W×L×H)		
Environment	18-25°C; RH: 40%-60%		

